



CONVECTOR

PRODUCT OPTIONS AND ACCESSORIES

- C0300/FS Lincat Convector Floor Stand for C0343M/C0343T Convection Ovens - with 4 Runners - W 660 mm
- C0300/LFSK Lincat Convector Low Floor Stand and Stacking Kit for C0343M/C0343T Convection Ovens - with 1 Shelf - W 660 mm

PRODUCT FEATURES

- 4 x GN1/1 capacity
- Touchscreen control with easy-to-use icon-driven menu selections
- Easy-view traffic light status - see the status of the oven at a glance, even in the noisiest kitchens
- Space for 24 programs with up to four stages, which can be adjusted individually
- Up to four-stage phased cooking for perfect results - set temperature, time and fan speed for each stage
- Even heat distribution thanks to electronically controlled two-speed, bi-directional fan
- Nine-hour on-screen timer, with electronic buzzer, and flashing oven lamps to indicate that cycle has finished
- Side opening door
- Timer range 1 - 540 minutes
- Shelf spacing 85mm

The perfect addition to any commercial kitchen, the Touch C0343T with intuitive touch screen menu provides the wider functionality and greater control that only a touch screen can deliver.

AIA FILE NUMBER:

ITEM NUMBER:



LINCAT CONVECTOR ELECTRIC COUNTER-TOP CONVECTION OVEN

- W 660 MM - D 740 MM - 3.0 KW

MODEL: C0343T

WEIGHTS & DIMENSIONS

Width	660 mil
Depth	740 mil
Height	600 mil
Weight	68.7 kg

SHIPPING DETAILS

Ship Width	88 cm
Ship Depth	100 cm
Ship Height	81.5 cm
Ship Weight	75.57 kg
Ship Method	LTL Common Carrier
Shipping Package Type	Pieces
Shipping Origin Zip Code	LN6 3QZ, UNITED KINGDOM
Quick Ship Product	No

WATER, PLUMBING, AND DRAINAGE SPECS

Water Line Required	No
Drain Line Required	No

PRODUCT CERTIFICATIONS



ENERGY SPECS

Primary Energy Type	Electric	Electrical Plug Type	UK 3-Pin Plug
Electrical Total Amperage	13 A	Number of Electrical Plugs	1
Electrical Volts	230V	Electrical Connection Type	Cord and Plug
Electrical Total Wattage	3000 W	Number of Electrical Conductor Wires	1
Electrical Kilowatts	3 kW	Dedicated Circuit Required	Yes
Electrical Phase	1-Phase	Electrical Remarks	Single

ADDITIONAL SPECIFICATIONS

Capacity (Volume)	72 l	Full-Size Or Half-Size	Half-Size
Construction Materials	Stainless Steel	Gastronorm Capacity	4 x GN1/1
Control Type	Electronic	Interior	Stainless Steel
Cooking Chamber Depth	550 mm	Number Of Cooking Chambers	1
Cooking Chamber Height	398 mm	Number of Pans	4
Cooking Chamber Width	330 mm	Number of Wire Racks	4
Cooking Rack Depth	325 mm	Sheet Pan Capacity	4 x 460mm x 330mm
Cooking Rack Width	530 mm	Type of Lighting	Halogen
Door Construction	Single Door	Ventless Cooking Technology	No
Door Hinge Type	Left Hang Hinge	Standard Depth Or Bakery Depth	Bakery Depth
Door Type	Stainless Steel With Viewing Glass	Temperature Maximum	260 °C
Fan Type	Bi-Directional	Temperature Minimum	60 °C

Lincat reserves the right to modify specifications or discontinue models without incurring obligation. Dimensions nominal.

Document Auto-Generated
March 24, 2025

BIDDING SPECIFICATIONS (SHORT FORM SPECS)

Bidding Specifications Not Available.

TECHNICAL DRAWING

