




FRIIA CHILLER/ CARBONATOR

- > Cold and/or sparkling: 35-45 L/hour
 - External CO₂ required
 - Aluminium block cooling technology
- > Suitable for: Offices, Hotels, Transport, Institutions, Cafes

CHILLER/CARBONATOR 1000053/1000052



SYSTEM SET-UP for Cold/Sparkling



SPECS

PRODUCT INFO		SIZE	PERFORMANCE SPECS		PLUMBING, ELECTRICAL & TECHNICAL SPECS		
NAME ORDER CODE	DIMS (D X W X H mm)	L/HR	CUPS /HR	POWER @220v	PLUMBING REQS	COMPRESSOR POWER	REFRIGERANT
FRIIA Chiller 1000053 FRIIA Carbonator 1000052	497 x 282 x 421	30-45l/hr based on incoming water temp of 15°C and output water temp of 5-7°	175-235 (ΔT = 10 °C)	180 W	3/4" BSP	1/8hp	R290

A minimum operating pressure of 2 bar or 28 psi downstream of filter is required for optimum output l/min.

PACKAGING

NAME	DIMENSIONS (L X W X H mm)	WEIGHT	QTY PER PALLET
FRIIA Chiller/Carbonator	400 x 600 x 580	41kg	8